

### Laundry accessory guide

February 2024

This quick reference guide to laundry accessories will help to make sure you have what you need for a successful installation in just 3 easy steps.

**Step 1** Find your model number.

**Step 2** Read the information on required and optional accessories to determine your needs and prepare yourself by knowing the answers to the following questions.

☐ Gas or electric dryer?

☐ Side-by-side or stacked installation?

 $\hfill\Box$  If installing side-by-side, do you want pedestals?

☐ If purchasing a gas dryer, is your home natural gas (NG) or liquid propane (LP)?

**Step 3** Identify the items you need to purchase for your laundry appliance.

#### Where to purchase accessories

Accessories can be purchased in-store with unit, or from LG Canada Parts & Accessories:

Shop online at LGCanadaParts.com

Call 1-855-341-2732



#### Contents

Washlower™2
Washers3
Dryers 4
WashCombo™5
Styler6





## LG WashTower™ accessory guide

			SWWE50N3* WKEX300HBA* WKEX200HBA* WKE100HWA	WKGX201HBA*	WKHC252HBA	WKHC152HWA
Water supply requirements		Required purchase	Washer water supply hoses (hot & cold)			
Washers must be connected to cold and hot water supplies (hot water supply requires a temperature range		Required purchase	Dryer water supply hoses (cold) (only required for steam dryers with * in listing a	bove)	Not applicable	
between 120°F and 130°F). Required min. / max. water pressure is 20 –120 psi.		Included	All WashTower™ laundry machines with steam drying (listed with * above) come s Y-connector	Not applicable		
		Included	3-Prong power cord for washer			
		Required purchase	Washer power cord connects to a 120 V, 60 Hz, 3-prong outlet			
Electrical requirements  LG WashTower™ laundry machines have 2 power cords attached to the unit.	0	Included	4-Prong power cord for dryer	3-Prong power cord for dryer	4-Prong power cord for dryer	
		Required purchase	Dryer power cord connects to a 240 V, 30 Amp circuit	Dryer power cord connects to a 120 V, 15 Amp circuit	Dryer power cord connects to a 240 V, 30 Amp circuit	
Dryer venting requirements (Note: Venting ductwork is not provided and should be		Required purchase	All vented dryers require a dryer vent kit (All dryers are shipped for rear venting, side vent kits are available, see below)	Not required		
purchased separately, if required. Gas dryers must vent to the outside. For gas dryers, your laundry room must have a rigid gas supply line to your dryer.)		Required purchase	Not applicable	Gas dryers require a flexible stainless steel gas connector kit	Not applicable	
LP conversion kit  If ordering a gas dryer and your home uses liquid propane (LP) instead of natural has (NG), order an LP conversion kit.	Propane	Required purchase	Not applicable	Not applicable		
Side vent kit  All dryers are shipped for rear venting. Order a side adapter kit to change venting to the side. (Right side venting is not available on gas dryers)	A CO	Optional purchase	Side vent kit – 3911EZ9131X (Only required if you are not venting from the rear)  Not applicable			
Drying rack  Order a drying rack to gently dry shoes, delicate sweaters and more, without tumbling.	5	Optional purchase	Drying rack included with SWWE50N3 Drying rack for 27" models (3750EL1001A) - purchase separately for WKEX300HWKHC202HBA Drying rack for 24" model (3751EL1002M) - purchase separatley for WKHC152H		KE100HWA, WKGX20	1HBA,

WashTower™ with electric dryer



Call 1-855-341-2732

WashTower™ with

gas dryer

WashTower™ with heat pump dryer

(no venting required)

## LG washer

accessory guide			WM8900HBA  WM3850HVA	WM6700HBA  WM3600HWA	WM6500HBA  WM3400CW	WM5500HVA	WT8600CB  WT7155CW	WT8405C_(B/W)	WT6105CW	WM1455HWA		
Water supply requirements Washers must be connected to cold and hot water supplies (hot water supply requires a temperature range between 120°F and 130°F). Required min. / max. water pressure is 20–120 psi.		Required purchase	Washer water si	upply hoses (hot & (	cold)							
Electrical requirements			ded 3-Prong power cord for washer									
Washers have a power cord attached to the unit.	Washers have a power cord attached to the unit.  Required purchase			Washer power cord connects to a 120 V, 60 Hz, 3-prong outlet								
Pedestal What is a side by side		Optional purchase	(only for use wit WM3850HVA, V 29" Pedestal – V	3 5/8" H) - WDP6_ th WM6700HBA, W WM3600HWA, WM3 WDP5B th WM8900HBA)	M6500HBA, WM55	500HVA,	Not applicable			Not applicable		
When installing side-by-side, you can add a pedestal or an LG SideKick™. (Be sure to order the correct colour to match your pair.)		Optional purchase	27" LG SideKick <sup>™</sup> pedestal washer – WD300C_ (V, B, W) (Includes all hoses and connectors) (only for use with WM6700HBA, WM6500HBA, WM5500HVA, WM3850HVA, WM3600HWA, WM3400CW)  29" LG SideKick <sup>™</sup> pedestal washer – WD200CB (Includes all hoses and connectors) (only for use with WM8900HBA)		Not applicable		Not applicable					

Front load washers



Compact front

load washer

Top load washers

### LG dryer accessory quide

				diyers
accessory guide			DLEX8900B DLEX6700B DLEX6500B DLEX5500V DLEX3850V DLE3600W DLGX5501V DLG3601W  DLE3400W DLEX8600BE DLE8400_(BE/WE) DLE7150W DLE6100W	DLHC6702B DLHC5502V  DLHC1455W
		Included	Steam dryer water supply hoses (cold) (only included with DLEX7900_, DLEX7300VE, DLEX7250W)	
Water supply requirements		Required purchase	Steam dryer water supply hoses (cold) (sold separately for DLEX8900B, DLEX6700B, DLEX6500B, DLEX5500V, DLGX5501V, DLEX3850V)	Not applicable
Dryers must be connected to a cold water supplies.		Included	Y-connector already included with all steam dryers (DLEX8900B, DLEX6700B, DLEX6500B, DLEX5500V, DLEX7800_(BE/VE), DLEX7300VE, DLEX7250W)	Not applicable
		Included	4-Prong power cord 3-Prong power cord	4-Prong power cord
<b>Electrical requirements</b> Dryers have a power cord attached to the unit.		Required purchase	Dryer power cord connects to a 240 V, 30 Amp circuit  Dryer power cord connects to a 120 V, 15 Amp circuit	Dryer power cord connects to a 240 V, 15 Amp Circuit (DLHC1455W 30 Amp circuit)
Dryer venting requirements (Note: Venting ductwork is not provided and should be			All vented dryers require a dryer vent kit (All dryers are shipped for rear venting, side vent kits are available, see below)	Not applicable
purchased separately, if required. Gas dryers must vent to the outside. For gas dryers, your laundry room must have a rigid gas supply line to your dryer.)			Gas dryers require a Not applicable flexible stainless steel gas connector kit	Not applicable
LP conversion kit  If ordering a gas dryer and your home uses liquid propane (LP) instead of natural has (NG), order an LP conversion kit.	Propane	Optional purchase	Not applicable  LP conversion kit - 383EEL3002R	Not applicable
Pedestal When installing side-by-side, you can add a pedestal. (Be sure to order the correct colour to match your pair.)		Optional purchase	27" Pedestal (13 5/8" H) – WDP6_(V, B, W) (only for use with DLEX6700B, DLHC6702B, DLEX6500B, DLEX5500V, DLEX3850V, DLE3600W, DLE3400W)  29" Pedestal – WDP5B (only for use with DLEX8900B)  24" DLHC1455W - has no matching pedestal	DLHC5502V, DLGX5501V,
Stacking kit When installing in a stacked configuration, you must order a stacking kit.		Optional purchase	27" Stacking kit – KSTK4 (DLEX6700B, DLEX6500B, DLEX5500V, DLGX5501V, DLEX3850V, DLE3600W, DLE3400W) 27" Heat pump stacking kit - HSTK1B (DLHC6702B, DLHC5502V) 29" Stacking kit – KSTK2 (DLEX8900B) 24" Stacking kit - 5001EL2001H included (DLHC1455W)	
Side vent kit  All dryers are shipped for rear venting. Order a side adapter kit to change venting to the side. (Right side venting is not available on gas dryers.)	A C	Optional purchase	Side vent kit – 3911EZ9131X (only required if you are not venting from the rear)	Not Applicable
Drying rack Order a drying rack to gently dry shoes, delicate sweaters		Optional purchase	Front load drying rack - 3750EL1001A (DLEX6700B, DLHC6702B, DLEX6500B, DLEX5500V, DLHC5502V, DLGX5501 DLE3600W, DLE3400W)  Top load drying rack - 3750EL0001C (DLEX7900_(BE/VE), DLEX7300VE, DLEX7250W, DLE7150W, DLE6100W)	V, DLEX3850V,

Electric dryers



Heat pump

dryers

Gas dryers

### LG WashCombo™ accessory guide

27" All-in-One
Washer/dryer WashCombo™

#### 24" All-in-One Washer/dryer WashCombo™







WM3998HBA

WM6998HBA

BA WM3555HVA

		WWW.SSSCIER				
Water supply requirements Washers must be connected to cold and hot water supplies (hot water supply requires a temperature range between 120°F and 130°F). Required min. / max. water pressure is 20–120 psi.	Required purchase	Washer water supply hoses (hot & cold)				
Floridation	Included	3-Prong power cord				
Electrical requirements	Required purchase	WashCombo™ power cord connects to a 120 V, 60 Hz grounded 3-prong outlet (15 Amps)				
Dryer venting requirements	Not applicable	Ventless HeatPump™ drying does not require venting	Ventless condensing drying does not require venting			
Pedestal You can add a pedestal or an LG SideKick™. (Be sure to order the correct colour to match your WashCombo™)	Optional purchase	Pedestal – WDP6B	Not applicable			
	Optional purchase	LG SideKick™ – WD300CB (Includes all hoses and connectors)	Not applicable			



# LG styler accessory guide





			S5MSB	S3MFBN			
Water supply requirements  Stylers do not connect to a cold or hot water supply. This allows for installation in any room of the home, as there		Included	Styler is equipped with 2 water tanks - a fill tank and a d (These tanks are manually filled and emptied)	rain tank			
are no permanent plumbing requirements.	A STATE OF THE STA	Included	Drip tray is included and used to catch any drips that may occur when filling or emptying the water tanks				
		Included	3-Prong power cord				
Electrical requirements		Required purchase	Connects to a 120 V, 60 Hz grounded 3-prong outlet (15 Amps)				
Dryer venting requirements		Not applicable	Ventless HeatPump™ drying does not require venting				
		Included	2 Rear leveling feet included - AFC72755402 Rear leveling feet may be used to ensure proper leveling				
Leveling		Included	4 Carpet spikes included - MFA63122901 If installed on carpet, additional carpet spikes may be used for added stability				
		Included	2 Non skid pads included  Depending on the type of flooring, non skid pads may be used to prevent shaking and shifting when opening t door				
Regular hanger	5-	Included	3 hangers included (5 hanger slots available) Regular hangers - AEE73009503	3 hangers included (3 hanger slots available)			
Pants hanger		Included	1 Pants hanger included - AEE73189701				
Shelf		Included	1 Shelf included - AHT74073801				

